

FINAL INSPECTION CHECKLIST

16" & 20" Slickline Sheave

S/N _____

- ___ Hub grease witnessed prior to seal.
- ___ Axle nuts are properly preloaded.
- ___ Wheel spins without excessive force.
- ___ Axle protrudes equally from each side.
- ___ 2 each spiral pins are centered in axle nuts.
- ___ 4 each spiral pins are present for locking pins.
- ___ Cover can be rotated out of top block without binding.
- ___ Locking pins retract and return without binding.
- ___ Locking pins are lubricated.
- ___ Shrouds are seated in recess and screws are tight.
- ___ Clevis rotates freely but is not loose.
- ___ White rigup washer present.
- ___ Hook latch retracts and closes with tension.
- ___ Cotter pin is fixed about clevis nut.
- ___ Handguard bushings are swaged and the inside diameters are chamfered on both sides.
 Check fit with ball lock pin.
- ___ Serial numbers on wheel tag and shop traveler agree.
- ___ Line size on wheel, wheel tag, and shop traveler agree.
- ___ Serial numbers and lot numbers on parts match shop traveler.
- ___ Overall appearance is good, no damage to paint or anodize.

I certify that the above-specified items have been inspected and found to be in compliance.

SIGNATURE _____ DATE _____